

Paradox SP7000 Intrusion Alarm System



Your complete Performance Solution

Intrusion Alarm System



Package Alarm Paradox 16 Zone

- 1 Unit LED 32 Zone Keypad
- 1 Unit Panel Board SP7000 Paradox
- 1 Unit Backup Battery 7AH 12V (Backup To 3 Day)
- 1 Unit Transformer 3Amp 12V
- 1 Unit Indoor Siren
- 1 Unit Outdoor Siren & Siren Metal Box
- 1 Unit Strobe Light
- 1 Unit LED System
- 1 Unit Built- in Voice Dialer Module

Features :

- Allow to disable or enable alarm through mobile phone
- Allow to manage or monitoring alarm setting and status through mobile phone
- Built-in remote control plug (Optional)
- 4 personal reporting dialing number

Add On :



Paradox keypad



Magnetic Sensor



Vibration Sensor



Pir Sensor



Remote Control



Indoor Siren



Outdoor Siren
Full Set



Roller Shutter
Plastic



Roller shutter
Metal



VTV ELECTRONIC SDN BHD & VTV SECURITY SERVICE CENTRE

Lot 7-1, 1st Floor, Block A, Lintas Square, Jalan Lintas, 88300 Kota Kinabalu, Sabah. Tel : +088-233-466, HP : 012-813-3189

V SECURITY SYSTEM

KM 11 1/4, Jalan Putatan, Kota Kinabalu, Sabah. (sebelah Kiong Li Timber) Tel : +088-773-080, HP : 012-885-0308

VSR SECURITY SYSTEM

Block A, No.11, Tropical Umbrella Industrial, Jalan Arsat 87012 Labuan W.P. Labuan Tel : +087-443-189, HP : 012-878-3189

Paradox SP7000

Intrusion Alarm System



Your complete Performance Solution

Intrusion Alarm System



- Supports StayD mode
- 4-wire expansion bus
- Expandable to 32 zones
- Expandable to 16 PGMs
- 2 Partitions
- 32 User Codes
- Supports PCS Series
- Supports IP100 Internet Module
- Supports VDMP3 Plug-in voice dialer
- Supports REM3 hand-held remote keypad - require RTX3 V1.31 or higher (SP4000 - One way only)
- Supports iParadox app
- In-field firmware upgradeable via a 307USB
 - WinLoad for SP5500/SP6000/SP7000
 - InField Firmware Upgrade Software for SP4000/SP65
- Menu-driven programming for the Installer, Master and Maintenance codes
- Multiple phone numbers: 3 for monitoring station, 5 for personal dialing and 1 for pager reporting (SP65: via PCS200 only - GSM reporting)
- Patented 2 opto coupler dialer circuit - the most reliable dialer in the industry - US Patents 5751803, RE39406 (N/A with the SP65)
- Automatic Daylight Savings Time feature
- Push button software reset (reset to default values and restart)
- Direct connect at 9.6k baud
 - WinLoad for SP5500/SP6000/SP7000
 - Babyware for SP4000/SP65
- 256 events buffered
- Fits in 20cm x 25.5cm x 7.6cm (8in x 10in x 3in) and 28cm x 28cm x 7.6cm (11in x 11in x 3in) metal boxes

Feature	SP7000
On-board Zones	16 (32w/ATZ)
On-board PGMs	4
Alarm Relay	1
PGM +/- Trigger	√
2-Wire Smoke Detector Input	√
Switching Power Supply	1.5A

* = Optional



VTV ELECTRONIC SDN BHD & VTV SECURITY SERVICE CENTRE

Lot 7-1, 1st Floor, Block A, Lintas Square, Jalan Lintas, 88300 Kota Kinabalu, Sabah. Tel : +088-233-466, HP : 012-813-3189

V SECURITY SYSTEM

KM 11 1/4, Jalan Putatan, Kota Kinabalu, Sabah. (sebelah Kiong Li Timber) Tel : +088-773-080, HP : 012-885-0308

VSR SECURITY SYSTEM

Block A, No.11, Tropical Umbrella Industrial, Jalan Arsat 87012 Labuan W.P. Labuan Tel : +087-443-189, HP : 012-878-3189