



## 2 Megapixel Anti- Explosion Network High Speed Dome

### Features :

- Exd II CT6/DIP A21 TA, T6
- IP68 protection level
- Double-deck stainless steel design and heat dissipation design
- Sony high performance sensor with exquisite image
- 1/3" CMOS progressive scan COMS, up to 2Mega
- Max. resolution as 1920\*1080
- Min. illumination : Colour 0.05lux@F1.6
- Infrared cut fitter
- DWDR & 3D DNR
- Standard API interface for developing & supportable for SDK, Onvif, CGI and PSIA accession
- 3D intelligent positioning, click-tracking and zooming in is reliable with DVR/Client software/IE
- Power-off memory (automatic recovery of PTZ and lens status)
- Support NAS storage, ANR is supportable. At most 8 NAS disk are supportable
- Auto-tracking is available under panoramic status
- Optional intelligent analysis



Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	Color: 0.05Lux @(F1.4, AGC ON), White: 0.005Lux @(F1.4, AGC ON)
Day & Night	ICR
Optical Zoom	20X
Digital Zoom	16X
Max. Resolution	1920 x 1080
Frame Rate	50Hz: 25fps(1920 x 1080) 60Hz: 30fps(1920 x 1080)
Pan Speed	Manual Speed : 0.1°- 300°/s, Preset Speed : 540°/s
Tilt Speed	Manual Speed : 0.1°- 240°/s, Preset Speed : 400°/s
Pan Range	360°endless
Tilt Range	-5°- 90°(Auto Flip)
Features	WDR, BLC, 3D DNR, Private masking, ROI encoding, Patrol, Pattern, Smart tracking, IP68