

SN-ADR22/04HB/E1

1080P 4CH !HDD Hybrid DVR



Key features

- ☒ Support AHD/TVI 1080P series front-end real-time encoding;
- ☒ Support VGA, HDMI 1080P HD output;
- ☒ Support InviewPro3 Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- ☒ Support various mobile monitoring: (IOS, Android)
- ☒ Support multiple web browsers (Firefox) ;
- ☒ Support more than languages, no nation boundaries;
- ☒ Perfect protection circuit, unique triple watchdog function;
- ☒ Supporting web, IMS, provide SDK development

Interface:



Dimension:



Specifications

VIDEO	
VideoCompression	H.264High Profile
EncodeAbility	4ch*1080P@ 15fps
DecodeAbility	4ch*1080P@ 15fps
Video Input	Pure Analog4ch*1080P Mixed Input: 2ch*1080P(AHD)+2ch*1080P(TVI) 2ch*1080P(AHD)+2ch*1080P(Network) 2ch*1080P(TVI)+2ch*1080P(Network) Pure Network4ch*1080P/4ch*960P/4ch*720P
AUDIO	
Audio Compression	G711A
Two Way Audio	Support
RECORD AND PLAYBACK	
Hard Drive	1 SATA(Each maximum support 6T)
Record	Manual/Event/Timer
Playback	4ch(pure local input mode)
STORAGE AND BACKUP	
Space Occupation	960H: 12~20G/ day*channel
	720P: 10~20G/ day*channel
	1080P 20~30G/ day*channel
	Audio: 691.2M/ day*channel
Backup Mode	USB HDD
INTERFACE	
Video Input	4ch BNC (AHD/TVI/CVBS)
Video Output	1ch VGA,1ch HDMI
Audio Input	4ch RCA
Audio Output	1ch RCA
Alarm Input	N/A
Alarm Output	N/A
Network Interface	1 RJ45 10M/100M Adaptive Ethernet Port
PTZ Control	RS485, Support Multiple PTZ Protocols
USB	2 USB
Hard Disk	1 SATA
GENERAL	
Power	DC12V/2A
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Dimension	255mm(L)x255mm(W)x45mm(H)