

SN-ADR22/04HB/E1

1080P 16CH 2HDD Hybrid DVR




Key features

- ☒ Support AHD/TVI 1080P series front-end real-time encoding;
- ☒ Support VGA, HDMI 1080P HD output;
- ☒ Support HDVI Cloud technology, easy to achieve a variety of network penetration, one step to remote monitoring, getting rid of various complicated network settings, easy and simple to operate;
- ☒ Support various mobile monitoring: (IOS, Android) .
- ☒ Support multiple web browsers (Firefox) ;
- ☒ Support more than languages, no nation boundaries;
- ☒ Perfect protection circuit, unique triple watchdog function
- ☒ Supporting web, IMS, provide SDK development

Interface:



Dimension:



Specifications

VIDEO	
Video Compression	H.264 High Profile
Encode Ability	16ch*1080P@15fps
Decode Ability	16ch*1080P@15fps
Videolnput	Pure Analog:16ch*1080P Mixed Input:8ch*1080P(AHD)+8ch*1080P(TVI) 8ch*1080P(AHD)+8ch*1080P(Network) 8ch*1080P(TVI)+8ch*1080P(Network) Pure Network:16ch*1080P/16ch*960P/16ch*720P
AUDEO	
Audio Compression	G711A
Two Way Audio	Support
RECORD AND PLAYBACK	
Hard Drive	2 SATA(Each maximum support 6T)
Record	Manual/Event/Timer
Playback	16ch(pure local input mode)
STORAGE AND BACKUP	
SpaceOccupation	960H:12~20G/ day*channel
	720P:10~20G/ day*channel
	1080P 20~30G/ day*channel
	Audio:691.2M/ day*channel
BackupMode	USB HDD
INTERFACE	
Video Input	16chBNC (AHD/TVI/CVBS)
Video Output	1ch VGA,1ch HDMI
Audio Input	6ch RCA
Audio Output	1ch RCA
Alarm Input	4ch
Alarm Output	1ch
Network Interface	1 RJ45 10M/100M Adaptive Ethernet
PTZ Control	RS485, SupportMultiple PTZProtocols
USB	2 USB
Hard Disk	2 SATA
GENERAL	
Power	12V/4A
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Dimension	350mm(L) 295mm(W) 45mm(H)